



# AUDIO SETS/

## AUDEOSB10P21

### Applications

- Retail shops
- Hotels, clubs, restaurants & bars
- Leisure, sport and health centres
- Multimedia presentations
- Museums and exhibitions
- Classrooms
- Meeting rooms
- Video-walls, screens, interactive
- AV marketing and digital signage

## Plug & Play Audio Set

ECLER ESSENTIALS AUDEO SB10P21 is a kit that will allow everybody to carry out an easy installation of a real professional 2.1 audio system: a stereo sound with a sub-woofer reinforcement unit.

This kit contains:

- AUDEOSB10P21 loudspeaker cabinet: a self-powered 10" sub-woofer unit combined with a built-in stereo amplifier that feeds satellite, full range loudspeakers
- Protection cover for connectors and local controls
- Wall panel control to adjust the set's volume remotely
- Speaker wire reel (50 meters), wall panel cable, screwdriver
- Quick installation guide, with a step-by-step detailed procedure



### Key Features

- 10" powered sub-woofer integrated in the cabinet, 150 WRMS
- 2 x 150 WRMS stereo amplifier integrated in the cabinet, with Euroblock connectors for external speakers ("satellites")
- Stereo audio input with RCA and Euroblock connectors
- Adjustable sub-woofer cutoff frequency: low-pass filter frequency between 100 and 150Hz
- sub-woofer phase switch
- MASTER VOL and SUB VOL level controls
- 0-10VDC ports for volume remote control, compatible with the WpmVOL wall panel
- ON / STANDBY, Signal Present, CLIP L and CLIP R indicators
- Recommended loudspeakers:
  - AUDEO Series: allows up to 8 loudspeakers (4 per channel - global impedance = 2Ω)
  - eAMBIT Series: allows up to 8 loudspeakers (4 per channel - global impedance = 2Ω)

Main Technical Specifications	Integrated Active Subwoofer Power	150 WRMS			
	Subwoofer Maximum SPL (dB@1m)	112 dB			
	Subwoofer LPF Crossover Filter	Adjustable from 100 to 150Hz / 12dB oct			
	Integrated Stereo Satellite Amplifier Power, per channel	119 WRMS @ 2Ω / 83 WRMS @ 4Ω			
	Integrated Stereo Satellite Amplifier Freq. Response	20Hz - 20kHz			
	Remote control	0- 10 VDC, compatible with WpmVOL wall panel			
	Others	Auto standby function			
	Dimensions/ Weight	310 mm	500 mm	425 mm	13.55 kg

### Accessories

- Wpm series wall panels



WpmVOL